

LORO-X DRAINJET® Siphonic parapet drains without roof penetration



made of stainless steel, according to DIN EN 1253

The complete system for new and reconstructed buildings with clamping and bonding flange, for bituminous and plastic roofing sheets. Complete system consisting of drain, pipes, fittings, sealing elements and clamps for installing the system in a fast and safe way.

- **as main drainage**
- **as emergency drainage**
- **in DN 50 and DN 70**

With LORO DRAINJET®-siphonic parapet drainage systems the roof or the heat insulation will not be penetrated.

The capacity of each complete system can clearly be proved with the help of the LORO-X data sheets, so that planning the drainage is uncomplicated and requires little time. The pressure-resistant LORO-X system of steel drainage pipes will ensure safe operations and easy installation on the construction site based on the reliable LORO-X push-fit socket.



Advantages:

- no penetration of the roof!
- no drainage pipes inside the building
- complete systems with a reliable certificate precisely to CAD design
- high drainage performance at a low roof water level
- connection with the roof covering and the vapor barrier in conformity with the standards
- pressure-resistant system of steel drainage pipes according to DIN EN standard 1123

LORO-X series 62 DRAINJET®-Parapet

without penetration into the roof

The specification in this Current

The LORO-X DRAINJET-Parapet drainage as a spout with gravity flow or in a complete system with siphonic flow is specified for planning, manufacture and execution as a roof drainage system with the following means, which are also available in the LORO-X Online Service.

The LORO-X internal and field service team looks forward to a personal discussion.



Optimisation qualities	3
Overview	4 - 5
Description	6 - 9
Applications	10 - 11
Dimensioning	12 - 13
Dimensions and weights	14 - 19
LORO-X data sheets	20 - 37
LORO-X online service	38 - 39
Contact	40

LORO roof drainage technology and specification

The LORO-X DRAINJET-Parapet drainage is also a roof drainage system that reliably provides for optimum drainage. The optimisation qualities correspond to the optimisation of certain features, which are presented with their optimisation values on page 3.

Roof drainage that reliably provides for optimum drainage necessitates a good specification and thus good communication between everyone involved in the task fields of research, development, planning, design, manufacturing, works, assembly, installation, distribution, consulting, testing, administration, patents and standards - with the support of the LORO internal and field service team.

When tendering the LORO drainage technology products that are bound to a tender, the precise specification is particularly important.

This Current is also a roof drainage technology product description, including the LORO-X data sheet with the precise, uniform features and feature values of each LORO-X roof drainage system, which supports a simple selection on the basis of the feature bar through the specification of a roof drainage system with objectively comparable features and illustrates the particular performance of the LORO-X roof drainage systems.

All LORO-X roof drainage systems are described by clear features for system shape and system performance, in particular the shape features, which are important for the performance features.

Series 62 LORO-X DRAINJET-Parapet without penetration into the roof

The 6 star optimisation qualities



Fast



Even with a low water level of just 15 mm above the congestion element, the patented weir under the hood ensures a strong discharge from the roof in case of emergency drainage. Ideal for roofs with a lightweight construction.



Sturdy



The suction effect of the downpipe propagates throughout the closed siphonic flow system as far as the drain and provides for a strong discharge from the roof.

Video at www.loro.de -> Service


Quiet



The patented suction cover enables a controlled water/air mixture that minimises cavitation and noise development.




Safe



Each complete system includes, as a proof of performance, a head-discharge curve measured under realistic conditions, which you can take from the respective LX specification sheet.

Space-saving



The drainage without penetration into the roof is also ideal for use with 'flat' thermal insulation. Since the complete system is mounted externally, the interior of the building can be freely used.



Money-saving



The high discharge rate even with a small nominal diameter reduces the number of necessary drains and pipes, making significant reductions possible in material usage and effort for the installation.


	Main drainage Siphone flow Silent-Power	
Roof penetration 	 0 mm	 0 mm
Diameter	DN 50	DN 70
LX-Number	LX 789	LX 636
Flange form	Clamping flange 90°	Clamping flange 90°
	Clamping flange 45°	Clamping flange 45°
	Bonding flange 45°	Bonding flange 45°
Weir height h [mm] 	0 mm	0 mm
Water height h [mm] 	55 mm	55 mm
Roof area A [m²]*	233	533
Discharge Q [l/sec] 	7,0 l/sec	16,0 l/sec
Schall (dB) 	Silent-Power	Silent-Power

*Assumptions: The roof area is calculated on the basis of the following assumptions:

local rainfall intensity, normal rain: $r_5 = 0.03 \text{ l/s/m}^2$

local rainfall intensity, heavy rain: $r_{100} = 0.06 \text{ l/s/m}^2$

Discharge coefficient C = 1 for smooth roof surfaces

Emergency drainage
Gravity flow
Silent
Siphonic flow
Silent-Power


0 mm

0 mm

DN 50	DN 50	DN 70	DN 70	DN 50	DN 50	DN 70
LX 1584	LX 1585	LX 1607	LX 1587	LX 1326	LX 1327	LX 637

Clamping flange 90°						
---------------------	---------------------	---------------------	---------------------	---------------------	---------------------	---------------------

Clamping flange 45°						
---------------------	---------------------	---------------------	---------------------	---------------------	---------------------	---------------------

Bonding flange 45°						
--------------------	--------------------	--------------------	--------------------	--------------------	--------------------	--------------------

40 mm	60 mm	40 mm	60 mm	40 mm	60 mm	50 mm
-------	-------	-------	-------	-------	-------	-------

75 mm						
-------	-------	-------	-------	-------	-------	-------

33	33	46	43	283	283	483
----	----	----	----	-----	-----	-----

1,0 l/sec	1,0 l/sec	1,4 l/sec	1,3 l/sec	8,5 l/sec	8,5 l/sec	14,5 l/sec
-----------	-----------	-----------	-----------	-----------	-----------	------------

Silent	Silent	Silent	Silent	Silent-Power	Silent-Power	Silent-Power
--------	--------	--------	--------	--------------	--------------	--------------

Save energy with know-how: **LORO-X DRAINJET-Parapet drainage systems** without penetration into the roof

Selected and installed – with a measured proof of performance

"With reliable siphonic flow via the parapet", designers and contractors can maximise the effectiveness and cost savings through the drainage of your projects, particularly in relation to refurbishment and emergency drainage.

The high-performance prefabricated parapet drainage system, as a construction kit from the discharge to the outlet, can be installed on every building with a parapet roof according to the measured system shape.

1. Selection (feature bar)

All important features for the selection can be found in the feature bar in the LX specification sheet. On the basis of the roof structure and the required discharge rate, the selection of a suitable complete system can be accomplished in a few minutes (e.g. by online calculation and configurator at www.loro.de).

2. Quotation (bill of materials)

On the basis of the bill of materials for the prefabricated roof drainage system in the LX specification sheet, a quotation can be prepared in a few minutes (e.g. by online tender). All system parts are hydraulically matched to one another. The height of the downpipe can be adapted to the building, but should be at least 4.2 m (according to measurement) for siphonic flow.


3. Installation (system drawing)

Since the high system performance is directly connected to the system shape, no system part may be exchanged within the chain of planning, ordering and installation without a prior hydraulic test! The complete system drawing, consisting of drains, pipes and fittings in the LX specification sheet, simplifies the coordination between all the trades on the building site. All LORO-X prefabricated roof drainage systems are pressure-resistant and backflow-safe, sustainable and dimensionally stable and are made of break-proof and shock-proof steel.

...with measured proof of performance (head-discharge curve)

Through the measurement of the prefabricated roof drainage system on one of the LORO-X test fields, the discharge rate is reliably proven and documented in the LX specification sheet as a head-discharge curve. This clear and standard-compliant proof of performance offers security for insurers and customers.

For each prefabricated roof drainage system there is an LX specification sheet available at www.loro.de as a PDF document for printing or mailing.



LORO Datenblatt LX 637 Attika-Schnellablaufsystems

Datenblatt LX 637 Datenblatt LX 637

Attikaentwässerung

Serie 62 Attika-DRAINJET® ohne Eingriff ins Dach

Notentwässerung
Druckströmung
Silent Power

Abfluss:	14,5 l/s
Wasserhöhe:	75 mm
Eingriffstiefe:	0 mm
Nennweiter:	DN 70
LX-Nummer:	LX 637
Wehrhöhe:	60 mm
Haube:	nicht belüftet
Falleitung:	nicht belüftet
Fallleitungshöhe:	ab 4,2 m
Entwässerung:	Im Freie

LX 637 Systemateile

1 x Art.-Nr. Ablass auf Seite 2 auswählen
 1 x Art.-Nr. 01401.070X, LORO-X Rohr mit einer Muffe
 1 x Art.-Nr. 13250.000X, LORO-Schraubenschlüssel
 1 x Art.-Nr. 00580.070X, LORO-X Bogen
 1 x Art.-Nr. 01011.070X, LORO-X Rohr mit einer Muffe
 1 x Art.-Nr. 00520.070X, LORO-X bogen

4 x Art.-Nr. 00971.070X, LORO-X Dichtelemente
 2 x Art.-Nr. 00973.070X, LORO-X Rohrschelle
 1 x Art.-Nr. 00980.000X, LORO-X Dichtmittel Tasse
 3 x Art.-Nr. 00805.000X, LORO-Sicherungsschellen
 2 x Art.-Nr. 09003.200X, LORO-X Stockschraube

hQ - Abflusskurve

CAD

Systemleistung

Wasserhöhe mm 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75


Abfluss l/s 3 5 8 10 13 14.2 14.3 14.4 14.5

Silent


Silent Power

AKTUELL SERIE 62 DJ ATTika

10

Example applications:**LORO-X DRAINJET®-Parapet****without roof penetration,****DN 70,****with clamping roof 45° for
bituminous roofing sheets****40 mm weir height****If you need an individual solution...**

The LORO-X service team will be happy to support you in the design of your individual roof drainage system! Either your selected LX standard system can be adapted by our roof drainage technicians to the individual properties of the building, or we will put together an individual complete system for your building with collecting pipe and several discharges on one downpipe.



Example applications:

LORO-X DRAINLET®-Parapet

without roof penetration,

DN 70,

with clamping flange 45° for

bituminous roofing sheets


40 mm weir height

Series 62

Discharge rate as spout:

Emergency drainage:

1.4 l/sec





Description

The LORO-X DRAINJET®-Parapet roof drainage system without penetration into the roof has a clamping flange.

- 1 LORO-X DRAINJET®-Parapet roof drainage system
- 2 Sealing sheets
- 3 thermal insulation
- 4 Vapour barrier
- 5 Trapezoidal sheet metal roof
- 6 LORO-Sliding flange
- 7 LORO-X Spout


System form




The LORO-X DRAINLET-Parapet drainage achieves a high discharge rate without penetration into the roof through the optimised congestion element under the hood.

Due to the large "overflow edge" of the congestion element, more water can discharge through the discharge pipe, which is installed at the same height, than would be possible with conventional spouts (installed higher).

The installation of the emergency drain takes place on the same level as the main drain, as a result of which additional work on the building site to set the emergency drain higher is unnecessary.

Fall 1: normal rain**Main drainage**

Fall 2: strong rain**Emergency drainage****Drainage: on floor**


Calculation

Calculation example*

- Parapet roof of a building with effective rainfall area A = 450 m² (no sub-areas)
- Discharge coefficient c = 1.0
- Rainfall r_{5,5} = 300 l/(s x ha)
- Rainfall r_{5,100} = 600 l/(s x ha)
- Water level for main drainage 55 mm
- Water level for emergency drainage 75 mm
- LORO-X DRAINJET-Parapet with siphonic flow for main and emergency drainage

Table 6 – Discharge coefficients C acc. to DIN 1986-100 for determining the rainwater discharge (excerpt)

No.	Type of surfaces	C*
1	Waterproof surfaces, e.g.	1,0
	- Roof areas	1,0
	- Concrete surfaces	1,0
	- Ramps	
	- Surfaces fastened in place with sealed joints	1,0
	- Blacktops (asphalt)	1,0
	- Paving with sealed joints	0,5
	- Gravel roofs	
	- Green roof areas	0,3
	- For intensive green roofs	
	- For extensive green roofs from 10 cm thickness	
	- For extensive green roofs below 10 cm thickness	0,3
		0,5



Required discharge of the main drainage

Determining the design rainfall intensity:

$$Q_r = \frac{A \cdot r_{5,5} \cdot C}{10000}$$

Q_r [l/s] = design rainfall intensity
 A [m²] = effective roof surface or partial surface
 r_{5,5} [l/(s · ha)] = Rainfall (5 min, every 5 years)
 C [-] = Discharge coefficient

$$Q_r = \frac{450 \cdot 300 \cdot 1,0}{10000}$$

$$Q_r = 13.5 \text{ l/s}$$

Required discharge of the emergency drainage

Determining the volumetric overflow rate for emergency drains:

$$Q_{em.} = \frac{A \cdot (r_{5,100} - r_{5,5} \cdot C)}{10000}$$

Q_{em.} [l/s] = volumetric overflow rate
 A [m²] = effective roof surface or partial surface
 r_{5,100} [l/(s · ha)] = Rainfall (5 min, every 5 years)
 C [-] = Discharge coefficient

$$Q_{em.} = \frac{450 \cdot (600-300 \cdot 1,0)}{10000}$$



$$Q_{em.} = 13.5 \text{ l/s}$$

Discharge values from

Specific. sheet LX 636

Specific. sheet LX 637

for the LORO-X DRAINJET-Parapet drainage



Available discharge of the main drainage

$$Q_{DA \text{ Main}} = 16.0 \text{ l/s}$$

Determination of the number of discharges for the main drainage

$$n_{DA} = \frac{Q_r}{Q_{DA \text{ Main}}} \quad \text{number of items}$$

n_{DA} [-] = number of main drainages
 Q_r [l/s] = discharge of the main drainage
 $Q_{DA \text{ Main}}$ [l/s] = discharge of a main drainage with a specified water level of 35 mm at the main drain

$$\frac{n_{DA}}{Q_{DA \text{ Main}}} = \frac{13.5 \text{ l/s}}{16.0 \text{ l/s}} = 1\text{-off}$$

Available discharge of the emergency drainage

$$Q_{DA \text{ Em.}} = 14.5 \text{ l/s}$$


Determination of the number of discharges for the emergency drainage

$$n_{Em.} = \frac{Q_{Em.}}{Q_{DA \text{ Em.}}} \quad \text{number of items}$$


$n_{Em.}$ [-] = number of emergency drainages
 $Q_{Em.}$ [l/s] = discharge of the emergency drainage
 $Q_{DA \text{ Em.}}$ [l/s] = discharge of an emergency drainage with a specified water level of 75 mm at the emergency drain

$$\frac{n_{Em.}}{Q_{DA \text{ Em.}}} = \frac{13.5 \text{ l/s}}{14.5 \text{ l/s}} = 1\text{-off}$$

Number of LORO-X DRAINJET-Parapet required
Main drainages = 1-off
Emergency drainages = 1-off




Please contact the LORO-X internal and field service team if you have any questions about the design of roof drainage.

Siphonic flow**Dimensions and weights**

**LORO-DRAINJET®
Siphonic parapet drain,
Series 62,
DN 50 and DN 70,
with clamping flange,
for bituminous roofing sheets**



made of stainless steel



**Discharge rate according to
specification sheet:**

LX 789 DN 50: 7,0 l/sec*
LX 636 DN 70: 16,0 l/sec*

DN 50: Art.-No. 01347.050X Weight: 8,4 kg
DN 70: Art.-No. 01347.070X Weight: 9,1 kg





**with clamping flange,
for bituminous roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX 789 DN 50: 7,0 l/sec*
LX 636 DN 70: 16,0 l/sec*

DN 50: Art.-No. 01351.050X Weight: 5,7 kg
DN 70: Art.-No. 01351.070X Weight: 6,5 kg



**with clamping flange,
for plastic roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX 789 DN 50: 7,0 l/sec*
LX 636 DN 70: 16,0 l/sec*

DN 50: Art.-No. 01353.050X Weight: 8,8 kg
DN 70: Art.-No. 01353.070X Weight: 9,2 kg

DN	d ₁	h
50	53	40
70	73	52

* Test specification according to DIN EN 1253

Siphonic flow

Dimensions and weights





**LORO-DRAINJET®
Siphonic parapet emergency drain,
Series 62,
weir height 40 mm, DN 50
with bonding flange,
for bituminous roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1326 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01349.050X Weight: 8,7 kg





**with clamping flange,
for bituminous roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1326 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01356.050X Weight: 8,7 kg



**with clamping flange,
for plastic roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1326 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01358.050X Weight: 8,7 kg

* Test specification according to DIN EN 1253

Siphonic flow

Dimensions and weights

LORO-DRAINJET®





**Siphonic parapet emergency drain,
Series 62,
weir height 60 mm DN 50,
with bonding flange,
for bituminous roofing sheets**

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1327 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01387.050X Weight: 6,0 kg



**Discharge rate according to
specification sheet:**

LX1327 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01359.050X Weight: 8,7 kg



with clamping flange, for bituminous roofing sheets

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1327 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01359.050X Weight: 8,7 kg









with clamping flange, for plastic roofing sheets

made of stainless steel

**Discharge rate according to
specification sheet:**

LX1327 DN 50: 8,5 l/sec*

DN 50: Art.-No. 01375.050X Weight: 8,7 kg



Siphonic flow

Dimensions and weights

LORO-DRAINJET®

**Siphonic parapet emergency drain, Series 62,
weir height 50 mm DN 70,
with bonding flange,
for bituminous roofing sheets**

made of stainless steel

Discharge rate according to specification sheet:

LX637 DN 70: 14,5 l/sec*

DN 50: Art-No. 01349.070X Weight: 6,0 kg

**with clamping flange,
for bituminous roofing sheets**

made of stainless steel

Discharge rate according to specification sheet:

LX637 DN 70: 14,5 l/sec*

DN 50: Art-Nr. 01356.070X Gewicht: 8,7 kg

**with clamping flange,
for plastic roofing sheets**

made of stainless steel

Discharge rate according to specification sheet:

LX637 DN 70: 14,5 l/sec*

DN 50: Art-No. 01358.070X Weight: 8,7 kg

Gravity flow

Dimensions and weights

LORO-DRAINLET®

Parapet emergency drain,


Series 62,

weir height 40 mm DN 50, DN 70,

with bonding flange,

for bituminous roofing sheets

made of stainless steel




Discharge rate according to specification sheet:

LX1584 DN 50: 1,0 l/sec

LX1607 DN 70: 1,4 l/sec

DN 50: Art.-No. 01397.050X Weight: 6,0 kg
DN 70: Art.-No. 01397.070X Weight: 6,0 kg



**with clamping flange,
for bituminous roofing sheets**


made of stainless steel

Discharge rate according to specification sheet:

LX1584 DN 50: 1,0 l/sec

LX1607 DN 70: 1,4 l/sec

DN 50: Art.-No. 01355.050X Weight: 6,0 kg
DN 70: Art.-No. 01355.070X Weight: 6,0 kg



**with clamping flange,
for plastic roofing sheets**

made of stainless steel

Discharge rate according to specification sheet:

LX1584 DN 50: 1,0 l/sec

LX1607 DN 70: 1,4 l/sec

DN 50: Art.-No. 01341.050X Weight 6,0 kg
DN 70: Art.-No. 01341.070X Weight: 6,0 kg

Gravity flow

Dimensions and weights

LORO-DRAINLET®

Parapet emergency drain,

Series 62,

weir height 60 mm DN 50, DN 70,

with bonding flange,

for bituminous roofing sheets




made of stainless steel

Discharge rate according to specification sheet:

LX1585 DN 50: 1,0 l/sec

LX1587 DN 70: 1,3 l/sec

DN 50: Art.-No. 01398.050X Weight: 6,0 kg
 DN 70: Art.-No. 01398.070X Weight: 6,0 kg



with clamping flange, for bituminous roofing sheets

made of stainless steel

Discharge rate according to specification sheet:

LX1585 DN 50: 1,0 l/sec

LX1587 DN 70: 1,3 l/sec

DN 50: Art.-No. 01357.050X Weight: 6,0 kg
 DN 70: Art.-No. 01357.070X Weight: 6,0 kg

with clamping flange, for plastic flange

made of stainless steel

Discharge rate according to specification sheet:

LX1585 DN 50: 1,0 l/sec




LX1587 DN 70: 1,3 l/sec

DN 50: Art.-No. 01347.050X Weight: 6,0 kg
 DN 70: Art.-No. 01347.070X Weight: 6,0 kg

Specification sheet LX 789**Siphonic Parapet drains
Series 62 DRAINJET®
without roof penetration****Main Drainage****Siphonic flow****Silent Power****Discharge rate:** 7,0 l/sec**Water height:** 55 mm**Roof penetration:** 0 mm**Diameter:** DN 50**LX-Number:** LX 789**Weir height:** 0 mm**Drain:** not ventilated**Downpipe:** not ventilated**Downpipe height:** min 4,2 m**Drainage:** in sewer**LX 789 Piece list**

1 x Art-No. choose drain on page two!
 1 x Art-No. 01401.050X, LORO-X Pipe with one socket
 1 x Art-No. 13232.050X, LORO-Sliding flange
 1 x Art-No. 00350.050X, LORO-X Bend
 1 x Art-No. 01101.050X, LORO-X Pipe with one socket
 1 x Art-No. 00550.050X, LORO-X Cleaning pipe

4 x Art-No. 00911.050X, LORO-X Sealing elements
 3 x Art-No. 00973.050X, LORO-X Pipe clamps
 1 x Art-No. 00986.000X, LORO-X Lubricant
 2 x Art-No. 00806.050X, LORO-X Anchor clips
 3 x Art-No. 09603.200X, LORO-X Threaded rods

**hQ - Head-Discharge curve****CAD****Systempower****Systemshape**


Water height	mm	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75
Discharge	l/sec					0,75	3	4,5	5,3	6	6,7	7,2	7,7	8		
		Silent											Silent Power			

Choose drain for piece list on page one!

LX789-1X

Drain Art.-No. 01358.050X


clamping flange 90°
for plastic roofing sheets



LX789-2X

Drain Art.-No. 01351.050X


clamping flange 45°
for bituminous roofing sheets



LX789-3X

Drain Art.-No. 01347.050X

bonding flange 45°
for bituminous roofing sheets



Please note:

For drainage systems with siphonic flow it is vital that only LORO-X pipes and fittings in the combination as indicated are used. Mixture or exchange of system parts may result in lower discharge capacities! The height of the downpipe must be a min. 4.2m for the indicated capacity to be obtained.



If roof drain and downpipe are fitted by different crews, then do follow the system setup acc. to the LX-data sheet at www.loro-x.com

Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 636**Siphonic Parapet drains
Series 62 DRAINJET®
without roof penetration****Main Drainage****Siphonic flow****Silent Power****Discharge rate:** 16,0 l/sec**Water height:** 55 mm**Roof penetration:** 0 mm**Diameter:** DN 70**LX-Number:** LX 636**Weir height:** 0 mm**Drain:** not ventilated**Downpipe:** not ventilated**Downpipe height:** min 4,2 m**Drainage:** in sewer**LX 636 Piece list**

1 x Art.-No. choose drain on page two!
1 x Art.-No. 01401.070X, LORO-X Pipe with one socket
1 x Art.-No. 13235.070X, LORO-Sliding flange
1 x Art.-No. 00350.070X, LORO-X Bend
1 x Art.-No. 01001.070X, LORO-X Pipe with one socket
1 x Art.-No. 05510.070X, LORO-X Stand pipe

4 x Art.-No. 00911.070X, LORO-X Sealing elements
3 x Art.-No. 00973.070X, LORO-X Pipe clamps
1 x Art.-No. 00986.000X, LORO-X Lubricant
2 x Art.-No. 00806.070X, LORO-X Anchor clips
3 x Art.-No. 09603.200X, LORO-X Threaded rods

**hQ - Head-Discharge curve****Systempower**

Water height	mm	10	15	20	25	30	35	40	45	50	55	60	65	70	75
Discharge	l/sec														
		Silent						Silent Power							


Systemshape

Choose drain for piece list on page one!

LX636-1X

Drain Art.-No. 01358.070X


clamping flange 90°
for plastic roofing sheets



LX636-2X

Drain Art.-No. 01351.070X


clamping flange 45°
for bituminous roofing sheets



LX636-3X

Drain Art.-No. 01347.070X

bonding flange 45°
for bituminous roofing sheets



Please note:

For drainage systems with siphonic flow it is vital that only LORO-X pipes and fittings in the combination as indicated are used. Mixture or exchange of system parts may result in lower discharge capacities! The height of the downpipe must be a min. 4.2m for the indicated capacity to be obtained. If roof drain and downpipe are fitted by different crews, then do follow the system setup acc. to the LX-data sheet at www.loro-x.com

Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1326

Siphonic Parapet drains Series 62 DRAINJET® without roof penetration

Emergency drainage

Siphonic flow

Silent Power

Discharge rate: 8,5 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 50

LX-Number: LX 1326

Weir height: 40 mm

Drain: not ventilated

Downpipe: not ventilated

Downpipe height: min 4,2 m

Drainage: on floor

LX 1326 Piece list

1 x Art.-No. choose drain on page two!

1 x Art.-No. 01401.050X, LORO-X Pipe with one socket
 1 x Art.-No. 13232.050X, LORO-Sliding flange
 1 x Art.-No. 00350.050X, LORO-X Bend
 1 x Art.-No. 01011.050X, LORO-X Pipe with one socket
 1 x Art.-No. 00320.050X, LORO-X Bend


4 x Art.-No. 00911.050X, LORO-X Sealing elements

2 x Art.-No. 00973.050X, LORO-X Pipe clamps


1 x Art.-No. 00986.000X, LORO-X Lubricant

3 x Art.-No. 00806.050X, LORO-X Anchor clips

2 x Art.-No. 09603.200X, LORO-X Threaded rods




hQ - Head-Discharge curve




Systempower

CAD



Systemshape




Water height	mm	10	15	20	25	30	35	40	45	50	55	60	65	70	75
Discharge	l/sec														
		Silent												Silent Power	

Choose drain for piece list on page one!

LX1326-1X


Drain Art.-No. 01358.050X

clamping flange 90°
for plastic roofing sheets
Weir height 40 mm


LX1326-2X


Drain Art.-No. 01356.050X

clamping flange 45°
for bituminous roofing sheets
Weir height 40 mm


LX1326-3X

Drain Art.-No. 01349.050X

bonding flange 45°
for bituminous roofing sheets
Weir height 40 mm



Please note:

For drainage systems with siphonic flow it is vital that only LORO-X pipes and fittings in the combination as indicated are used. Mixture or exchange of system parts may result in lower discharge capacities! The height of the downpipe must be a min. 4.2m for the indicated capacity to be obtained. If roof drain and downpipe are fitted by different crews, then do follow the system setup acc. to the LX-data sheet at www.loro-x.com

Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1327
Siphonic Parapet drains
Series 62 DRAINJET®
without roof penetration
Emergency drainage
Siphonic flow
Silent Power

Discharge rate: 8,5 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 50

LX-Number: LX 1327


Weir height: 60 mm

Drain: not ventilated

Downpipe: not ventilated



Downpipe height: min 4,2 m

Drainage: on floor


LX 1327 Piece list

- 1 x Art.-No. choose drain on page two!
 1 x Art.-No. 01401.050X, LORO-X Pipe with one socket
 1 x Art.-No. 13232.050X, LORO-Sliding flange
 1 x Art.-No. 00350.050X, LORO-X Bend
 1 x Art.-No. 01011.050X, LORO-X Pipe with one socket
 1 x Art.-No. 00320.050X, LORO-X Bend

- 4 x Art.-No. 00911.050X, LORO-X Sealing elements
 2 x Art.-No. 00973.050X, LORO-X Pipe clamps
 1 x Art.-No. 00986.000X, LORO-X Lubricant
 3 x Art.-No. 00806.050X, LORO-X Anchor clips
 2 x Art.-No. 09603.200X, LORO-X Threaded rods

hQ - Head-Discharge curve

Systempower
CAD

Systemshape


Water height	mm	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75
Discharge	l/sec															8,5
		Silent										Silent Power				

Choose drain for piece list on page one!

LX1327-1X

Drain Art.-No. 01375.050X


clamping flange 90°
for plastic roofing sheets
Weir height 60 mm



LX1327-2X

Drain Art.-No. 01359.050X


clamping flange 45°
for bituminous roofing sheets
Weir height 60 mm



LX1327-3X

Drain Art.-No. 01387.050X

bonding flange 45°
for bituminous roofing sheets
Weir height 60 mm



Please note:

For drainage systems with siphonic flow it is vital that only LORO-X pipes and fittings in the combination as indicated are used. Mixture or exchange of system parts may result in lower discharge capacities! The height of the downpipe must be a min. 4.2m for the indicated capacity to be obtained. If roof drain and downpipe are fitted by different crews, then do follow the system setup acc. to the LX-data sheet at www.loro-x.com

Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 637

Siphonic Parapet drains

Series 62 DRAINJET® without roof penetration

Emergency drainage

Siphonic flow


Silent Power

Discharge rate: 14,5 l/sec**Water height:** 75 mm**Roof penetration:** 0 mm**Diameter:** DN 70**LX-Number:** LX 637**Weir height:** 60 mm**Drain:** not ventilated**Downpipe:** not ventilated**Downpipe height:** min 4,2 m**Drainage:** on floor

LX 637 Piece list


- 1 x Art.-No. choose drain on page two!
 1 x Art.-No. 01401.070X, LORO-X Pipe with one socket
 1 x Art.-No. 13235.070X, LORO-Sliding flange
 1 x Art.-No. 00350.070X, LORO-X Bend
 1 x Art.-No. 01011.070X, LORO-X Pipe with one socket
 1 x Art.-No. 00320.070X, LORO-X Bend

hQ - Head-Discharge curve




Systempower

Water height	mm	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75
Discharge	l/sec								3	5	8	10	13	14,2	14,3	14,4
		Silent						Silent Power								



- 4 x Art.-No. 00911.070X, LORO-X Sealing elements
 2 x Art.-No. 00973.070X, LORO-X Pipe clamps
 1 x Art.-No. 00986.000X, LORO-X Lubricant
 3 x Art.-No. 00806.070X, LORO-X Anchor clips
 2 x Art.-No. 09603.200X, LORO-X Threaded rods

CAD



Systemshape


AKTUELL SERIE 62 DJ ATTICA ENG V6

Choose drain for piece list on page one!

LX637-1X

Drain Art.-No. 01358.070X


clamping flange 90°
for plastic roofing sheets



LX637-2X

Drain Art.-No. 01356.070X


clamping flange 45°
for bituminous roofing sheets



LX637-3X

Drain Art.-No. 01349.070X

bonding flange 45°
for bituminous roofing sheets



Please note:

For drainage systems with siphonic flow it is vital that only LORO-X pipes and fittings in the combination as indicated are used. Mixture or exchange of system parts may result in lower discharge capacities! The height of the downpipe must be a min. 4.2m for the indicated capacity to be obtained.

Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1584

Parapet drainage system

Series 62 DRAINLET®

without roof penetration

Emergency drainage

Gravity flow

Silent

Discharge rate: 1,0 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 50

LX-Number: LX 1584

Weir height: 40 mm

Drain: ventilated

Downpipe: ventilated

Downpipe height: -

Drainge: on floor

LX 1584 Piece list



1 x Art.-No. choose drain on page two!

1 x Art.-No. 01401.050X, LORO-X Pipe with one socket

1 x Art.-No. 13232.050X, LORO-X Sliding flange

1 x Art.-No. 00911.050X, LORO-X Sealing element


1 x Art.-No. 00986.000X, LORO-X Lubricant




Water height	mm	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
Discharge	l/sec	-	-	-	-	-	-	0,5	0,7	0,8	0,9	0,9	1,0	1,1	1,1	1,2	1,4	1,5
		Silent																

Choose drain for piece list on page one!**DN 50****LX1584-1X**


Drain Art.-No. 01341.050X

clamping flange 90°
for plastic roofing sheets
Weir height 40 mm**LX1584-2X**

Drain Art.-No. 01355.050X

clamping flange 45°
for bituminous roofing sheets
Weir height 40 mm**LX1584-3X**

Drain Art.-No. 01397.050X

bonding flange 45°
for bituminous roofing sheets
Weir height 40 mm**Heat tracing:** Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1585
Parapet drainage system
Series 62 DRAINLET®
without roof penetration
Emergency drainage
Gravity flow
Silent
Discharge rate: 1,0 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 50

LX-Number: LX 1585

Weir height: 60 mm

Drain: ventilated

Downpipe: ventilated

Downpipe height: -

Drainge: on floor



LX 1585 Piece list
1 x Art-No. choose drain on page two!

1 x Art-No. 01401.050X, LORO-X Pipe with one socket


1 x Art-No. 13232.050X, LORO-X Sliding flange

1 x Art-No. 00911.050X, LORO-X Sealing element

1 x Art-No. 00986.000X, LORO-X Lubricant


hQ - Head Discharge curve

Systempower

Water height	mm	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
Discharge	l/sec	-	-	-	-	-	-	-	-	-	0,3	0,8	1,0	1,1	1,2	1,2	1,3	1,3
Silent																		

CAD



Choose drain for piece list on page one!

DN 50

LX1585-1X

Drain Art.-No. 01344.050X


clamping flange 90°
for plastic roofing sheets
Weir height 60 mm



LX1585-2X

Drain Art.-No. 01357.050X


clamping flange 45°
for bituminous roofing sheets
Weir height 60 mm



LX1585-3X

Drain Art.-No. 01398.050X

bonding flange 45°
for bituminous roofing sheets
Weir height 60 mm



Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensibility. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1607

Parapet drainage system Series 62 DRAINLET® without roof penetration

Emergency drainage
Gravity flow
Silent

Discharge rate: 1,4 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 70

LX-Number: LX 1607

Weir height: 40 mm

Drain: ventilated




Downpipe: ventilated

Downpipe height: -

Draining: on floor

LX 1607 Piece list

- 1 x Art.-No. choose drain on page two!
 1 x Art.-No. 01401.070X, LORO-X Pipe with one socket
 1 x Art.-No. 13235.070X, LORO-X Sliding flange
 1 x Art.-No. 00911.070X, LORO-X Sealing element
 1 x Art.-No. 00986.000X, LORO-X Lubricant


hQ - Head-Discharge curve

CAD

Systempower
Systemshape

Water height	mm	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
Discharge	l/sec	-	-	-	-	-	-	-	0,5	0,7	1,0	1,2	1,4	1,6	1,8	2,0	2,1	2,2
Silent																		

AKTUELL SERIE 62 DJ ATTICA ENG V6


Choose drain for piece list on page one!

DN 70

LX1607-1X

Drain Art.-No. 01341.070X


clamping flange 90°
for plastic roofing sheets
Weir height 40 mm



LX1607-2X

Drain Art.-No. 01355.070X


clamping flange 45°
for bituminous roofing sheets
Weir height 40 mm



LX1607-3X

Drain Art.-No. 01397.070X

bonding flange 45°
for bituminous roofing sheets
Weir height 40 mm



Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Specification sheet LX 1587
**Parapet drainage system
Series 62 DRAINLET®
without roof penetration**
Emergency drainage
Gravity flow
Silent
Discharge rate: 1,3 l/sec

Water height: 75 mm

Roof penetration: 0 mm

Diameter: DN 70

LX-Number: LX 1587

Weir height: 60 mm

Drain: ventilated




Downpipe: ventilated

Downpipe height: -

Drainge: on floor

LX 1587 Piece list

- 1 x Art.-No. choose drain on page two!**
- 1 x Art.-No. 01401.070X, LORO-X Pipe with one socket
1 x Art.-No. 13235.070X, LORO-X Sliding flange
1 x Art.-No. 00911.070X, LORO-X Sealing element
1 x Art.-No. 00986.000X, LORO-X Lubricant


hQ - Head-Discharge curve

CAD

Systempower
Systemshape

Water height	mm	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
Discharge	l/sec	-	-	-	-	-	-	-	-	-	0,5	0,9	1,3	1,5	1,6	1,8	2,0	2,1
Silent																		

Choose drain for piece list on page one!

DN 70


LX1587-1X

Drain Art.-No. 1344.070X

clamping flange 90°

for plastic roofing sheets

Weir height 60 mm




LX1587-2X

Drain Art.-No. 01357.070X

clamping flange 45°

for bituminous roofing sheets

Weir height 60 mm




LX1587-3X

Drain Art.-No. 01398.070X

bonding flange 45°

for bituminous roofing sheets

Weir height 60 mm



Heat tracing: Lorowerk recommends to check all drains and pipes with regard to their frost-sensitivity. Where necessary, these parts should be upgraded with heat tracing.

Calculation of intensity of rainfall
1. Calculation

LORO-X Online Calculation (for Flat roof-Drainage)

- Calculate the amount of water that has to be drained
- Choose a LORO-X Scupper-Roof-Drainsystem from the suggestions based on the calculation
- Generate a tender for the System from the Drain to the Standpipe including LX-Data sheets

Please insert the Data of the Roof-Surface of your building

Name/Place of building:

Your Name:

Your Email:

Roofage in m²: m² (mandatory field)

Roof type (C): Concrete roof 1

Choose city:

Normal-Rainfall: (5.5) in Liter/Second/10.000m²

Maximum-Rainfall: (5.100) in Liter/Second/10.000m²

Dachfläche
Fallleitung

Dachgeometrie muss Wasserzufluss zu den Abläufen gewährleisten
- Füllung bei Druckentlastung mindestens 4 mm
Für die Auslast der Notentwässerung müssen gegeben sein

Calculate

Selecting the right ready-made system
2. Configurator

LORO-X Online Configurator

Please make the Online-Calculation! **406** available Systems please make more choices

Way of drainage	Type of drainage	Type of flow
Pipes outside (Scupper)	Main-Drainage	Gravity-flow
Pipes inside	Emergency-Drainage	Siphonic-flow
Dach-waagerechter Abgang	Main-Emergency-Combi	

Pipe diameter	Flange type/roof surface	Maximal roof penetration (for scuppers)
DN 40	(Scupper) Plastic 90° clamping flange (Scupper) bituminous 45° clamping flange (Scupper) bituminous 45° glue flange (Scupper) Plastic/bituminous	Maximal 106mm

Foto	LX-Number and short description	Number of Systems depending on Online-Calculation
	LX466-2X 45° clamping flange Not/Emergency: 17.6 l/s DN 70.	Choose System and show Systemdata in Productdatabase ►
	LX466-1X 90° clamping flange Not/Emergency: 17.6 l/s DN 70.	Choose System and show Systemdata in Productdatabase ►
	LX466-4X clamping flange without lip Not/Emergency: 17.6 l/s DN 70.	Choose System and show Systemdata in Productdatabase ►
	LX500-2X 45° clamping flange Not/Emergency: 8.6 l/s DN 50.	Choose System and show Systemdata in Productdatabase ►

www.loro-x.com -> Service -> Calculation



You need three measurements to calculate the necessary discharge rate:

- Roof area in square metres
- Roof structure
- Local intensity of rainfall

The result of the online calculation is the required discharge rate in litres per second. The calculated performance is transferred to the online configurator.

www.loro-x.com -> Service -> Configurator



With the LORO-X online configurator you can select the right LORO-X roof drainage system. The following features are taken into account:

- Drainage route (parapet or roof)
- Type of drainage (main or emergency)
- Type of flow (gravity or siphonic)
- Nominal diameter of the pipework system (DN)
- Connection to sealing sheet (bitumen or PVC)
- Penetration depth in the thermal insulation

After successful configuration you will see a list of usable LX systems "below" the configurator.

If you carried out online calculation beforehand the software automatically determines the necessary qty. of available LX systems.

The selected LX system along with the qty. is then transmitted to the LORO-X product database.

