

## Series 43 Parapet-Direct

		Main drainage							
		Gravity flow							
		Silent							
	<p><b>without roof penetration</b></p> <p><b>1</b> without basin</p> <p>01316X</p> <p>01331X</p> <p><b>2</b> with clamping flange for plastic sheets</p> <p>01333X</p>			<p><b>with basin</b></p> <p><b>3</b> with basin</p> <p>01330X</p> <p><b>4</b> as double pipe drain</p> <p>01320X</p>			<p><b>with basin and lowered pipe</b></p> <p><b>5</b> with basin and lowered pipe</p> <p>01350X</p> <p><b>6</b> as double pipe drain</p> <p>01324X</p>		
	<b>DN</b>	<b>70</b>	<b>100</b>		<b>70</b>	<b>100</b>		<b>100</b>	
	Roof penetration depth	0 mm	0 mm	0 mm	52 mm	52 mm	52 mm	103 mm	103 mm
	Water height (mm)	<b>35</b>	<b>35</b>	<b>35</b>	<b>35</b>	<b>35</b>	<b>35</b>	<b>35</b>	<b>35</b>
Weir height (mm)	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	
	<b>LX-No.</b>	<b>LX620</b>	<b>LX621</b>	<b>LX1110</b>	<b>LX650</b>	<b>LX647</b>	<b>LX653</b>	<b>LX694</b>	<b>LX727</b>
<b>Discharge Q (l/sec)</b>	11								
	10								
	9	<b>1</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b> 4,0 l/s
	8								
	7								
	6								
	5						4,5 l/s*	4,5 l/s*	4,0 l/s*
	4	0,8 l/s*	1,2 l/s*	1,7 l/s*	2,3 l/s*	3,0 l/s*			
	3								
	2								
	1								
									as Main Emergency Combination System**

\* Discharge capacity in keeping with test specification according to DIN EN 1253, downpipe length 4,2 m

\*\* As main emergency combination system with emergency overflow at the collecting box