

Series 62 DRAINJET® without roof penetration

	Emergency drainage									
	Gravity flow				Siphonic flow					
	Silent				Silent Power				Power	
	<p>with clamping flange</p> <p>01355X/01357X</p> <p>01341X/01344X</p>				<p>with clamping flange</p> <p>01356X/01359X</p> <p>01358X/01375X</p>				<p>with bonding flange</p> <p>01349X (Wehr 60 mm)</p> <p>01354X (Wehr 40 mm)</p>	
	<p>with bonding flange</p> <p>01397X/01398X</p>				<p>with bonding flange</p> <p>01349X/01387X</p>					
	DN	50	50	70	70	50	50	70	100	100
	Roof penetration depth	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm
Water height (mm)	75	75	75	75	75	75	75	75	75	
Weir height (mm)	40	60	40	60	40	60	50	40	60	
LX-No.	LX1584	LX1585	LX1607	LX1587	LX1326	LX1327	LX637	LX1157	LX1159	
Discharge Q (l/sec)									37,0 l/s*	36,0 l/s*
									40 Wehr 40 Wehr	60 Wehr 60 Wehr
	1,0 l/s**	1,0 l/s**	1,4 l/s**	1,3 l/s**	8,5 l/s*	8,5 l/s*	14,5 l/s*			
	40 Wehr 40 Wehr	60 Wehr 60 Wehr	40 Wehr 40 Wehr	60 Wehr 60 Wehr	40 Wehr 40 Wehr	60 Wehr 60 Wehr	50 Wehr 50 Wehr			

* Discharge capacity in keeping with test specification according to DIN EN 1253, downpipe length 4,2 m

** LORO measurement without downpipe as spout