

Series 79 RAINSTAR® with raised edge

	Main drainage						Emergency drainage												
	Gravity flow			Siphonic flow			Gravity flow				Siphonic flow								
	Silent Power						Silent Power												
	<p>with clamping flange</p>			<p>with clamping flange</p>			<p>01371X</p>				<p>with clamping flange</p>								
	<p>01370X</p> <p>01372X with bonding flange</p> <p>01374X</p>			<p>01380X</p> <p>01382X</p>			<p>01373X with clamping flange</p>				<p>01381X</p> <p>01383X</p>								
DN	50	70	100	50	70	100	50	70	100	40	50	70	100						
Roof penetration depth	82mm	92mm	106mm	82mm	92mm	106mm	82mm	92mm	106mm	76mm	82mm	92mm	106mm						
Water height (mm)	35	35	35	55	55	55	75	75	75	75	75	75	75						
Weir height (mm)	0	0	0	0	0	0	35	35	35	55	55	55	55						
LX-No.	LX490	LX489	LX460	LX467	LX479	LX483	LX492	LX461	LX480	LX494	LX493	LX465	LX469	LX481	LX485	LX682	LX500	LX466	LX482
Discharge Q (l/sec)																			

= as spout

* Discharge capacity in keeping with test specification according to DIN EN 1253, downpipe length 4,2 m

** LORO measurement with fully ventilated downpipe, corresponds to spout capacity